

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FP170 Range – 20180112

P1/3

- 1. Unique identification code of the product-type:** FP170 Range of Collars
- 2. Intended use/es:** These are pipe closure devices used to form penetration seals where combustible pipes, cables and metal pipes with insulation penetrate walls and floors.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026-2 edition 2011 used as European Assessment Document  
**European Technical Assessment:** ETA 17/0136 of 11/12/2017  
**Technical Assessment Body:** 0843 UL International (UK) Ltd  
**Notified Body:** 0843 UL International (UK) Ltd
- 7. Declared performance/s:**

Basic Work Requirement	Performance
<b>Mechanical resistance and stability</b>	
None	Not relevant
<b>Safety in case of fire</b>	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA17/0136 Annex A
<b>Hygiene, Health and the Environment</b>	
Air Permeability (EN 1026:2000)	NPD
Water Permeability (ETAG 026-3 Annex C)	NPD
Release of dangerous substances	Use categories: IA1, S/W3 Declaration of manufacturer
<b>Safety in Use</b>	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
<b>Protection against noise</b>	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
<b>Energy, Economy and Heat Retention</b>	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
<b>General Aspects Relating to fitness for use</b>	
Durability and Serviceability (EOTA TR 024:2009)	Y <sub>2</sub>

The performance of the product identified above is in conformity with the set of declared performance/s. This

P2/3

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**

M. Liptrot, Business Unit Director Sealants & Coatings



At Wigan on 16 January 2018

**Annex:**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

**No. FP170 Range – 20170428**

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

P2/3

<b>CE</b>	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 17 0843-CPR-0357 FP170 Range – 20180112 <a href="http://www.nullifire.com/FP170/">www.nullifire.com/FP170/</a>	
EN 1366-3: 2009 ETA 17-0136 ETAG 26, Part 2 These are pipe closure devices used to form penetration seals where combustible pipes, cables and metal pipes with insulation penetrate walls and floors.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	See ETA17/0136 Annex A
Hygiene, Health and Environment	
Air Permeability (EN 1026:2000)	NPD
Release of dangerous substances	Use categories: IA1, S/W3 Declaration of manufacturer
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	NPD
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Y <sub>2</sub>