DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FS700 - 20161014

1. Unique identification code of the product-type: FS700

2. Intended use/es: A fire resistant, one part acrylic based sealant used to form linear joint and gap seals where gaps are present in wall and floor constructions.

3. Manufacturer: tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK. WN2 4HT

5. System/s of AVCP: System 1

6. European Assessment Document: ETAG 026 edition 2011 used as EAD

European Technical Assessment: ETA 14/0355 of 10/10/2014
Technical Assessment Body: Warrington Certification Limited
Notified Body: 1121, Warrington Certification Limited

7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification	
Safety in Case of Fire			
Reaction to fire	Class E	EN13501-1	
Resistance to fire	Up to El180 Resistance to fire performance, in	EN13501-2	
	accordance with EN13501-2 See ETA 14/0355	EN1366-4: 2006	
	clause 3.2 - Annex C		
Hygiene, Health and Environment			
Dangerous Substances	See ETA 14/0355 Clause 3.5		
Energy, Economy and Heat Retention			
Service & Durability	Z ₂ intended for use in internal conditions with		
	humidity < 85% RH, temperatures > 0 °C, without	ETAG 026-3	
	exposure to rain or UV in accordance with EOTA		
	Technical Report TR024: 2009		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings At Wigan on 14 October 2016

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

No. FS700 – 20161014



CE

tremco illbruck Limited,
Coupland Road, Hindley Green, Wigan. WN2 4HT UK
14

1121-CPR-JA5052 FS700 – 20161014 www.nullifire.com/FS700/

> EN 1366-4: 2006 ETA 14-0355 ETAG 26, Part 3

A fire resistant, one part acrylic based sealant used to form linear joint and gap seals where gaps are present in wall and floor constructions.

Essential Characteristic	Performance		
Safety in Case of Fire			
Reaction to fire	Class E		
Resistance to fire	Up to El180 Resistance to fire performance, in accordance with EN13501-2 See ETA 14/0355 clause 3.2 - Annex C		
Hygiene, Health and Environment			
Dangerous Substances	See ETA 14/0355 Clause 3.5		
Energy, Economy and Heat Retention			
Service & Durability	Z ₂ intended for use in internal conditions with humidity < 85% RH, temperatures > 0 °C, without exposure to rain or UV in accordance with EOTA Technical Report TR024: 2009		
Other	NPD		